

EPOXIN-0M59

**Protection for
thermosetting,
thermoplastic, metal
and painted
surfaces**

FEATURES

- ✓ Water and oil repellency.
- ✓ UV protection
- ✓ It provides late contamination.
- ✓ Transparent
- ✓ Protects the surface against chemicals.
- ✓ Resistance to scratches.
- ✓ 10 years of protection.

CONTACT

- 🌐 www.epoxin.com.tr
- ✉ info@epoxin.com.tr
- ☎ +90 (216) 680 91 58

AREAS OF USE

- ✓ Metal and alloys
- ✓ Thermosets and thermoplastics
- ✓ Composite Materials
- ✓ Painted Surfaces
- ✓ All Vehicles
- ✓ Electronics vehicles

APPLICATION

- ✓ The surface should be cleaned of dirt, dust, water, oil and detergent residues before application and the application should be made on a dry surface.
- ✓ The application should be made in a way that is not directly exposed to the sun.
- ✓ Place the suede fabric, on the sponge surface. Pour a sufficient amount of the product onto the suede fabric, spread it over an area of 1 sqm with diagonal movements. When the pilling starts, wipe it with a microfiber cloth.
- ✓ Curing : 48 hours

PACKAGING

- ✓ 1 ltr covers 200 sqm.
- ✓ 1 Ltr, 5 Ltr, 30 Ltr

